



Dell Precision R5400

The Dell Precision™ R5400 is a high-performance dual-socket 2U rack workstation that provides an industry-standard alternative to blade workstations providing fully scalable high-performance graphics options.

A rack workstation that is big on performance and flexibility

Looking for a high-end workstation that delivers world-class performance and exceptional processing and graphics power, but is engineered for a high-density rack environment? Look no further. Developed in close collaboration with hardware and software partners, the Dell Precision R5400 rack workstation delivers no-compromise, high-performance workstation technologies in a flexible 2U chassis — an ideal solution for centralizing critical customer data and workstation assets in secure locations (data centers, OEM customer enclosures, etc.). This is particularly attractive for high-performance clusters/render farms, crowded heat and acoustically sensitive environments like financial trading or factory floors. Optimized for performance, reliability and scalability in environments where space is at a premium, the Dell Precision R5400 lets you power through complex tasks with configuration options simply not available on blade workstations today.

Visual realism with high-performance open GL graphics

Dell Precision workstations offer an intelligent selection of high-performance graphics cards that can satisfy a range of customer needs, from outstanding OpenGL® 3D performance to dependable 2D performance. With its two PCIe x16 slots, the Dell Precision R5400 is well equipped to house high-performance graphics cards to help meet the toughest of visualization challenges. Select from a wide range of industry-standard cards while retaining the option to change or upgrade at a later date.

Optimal scalability in a compact 2U chassis

The Dell Precision R5400 provides a highly scalable, cost-effective architecture that can easily be housed in a rack without the expense and potential redundant rack space associated with an enclosure for blades. Workstations address many different user needs and run a wide variety of applications, using graphics and other industry standard cards. The flexibility of this rack workstation is enhanced by a choice of PCI, PCIx or PCIe slot combinations — in addition to the graphics slots — making it easy to optimize for a particular solution.

Peace of mind through ISV application certification

Dell partners with leading ISVs to certify¹ system and application compatibility, ensuring optimized performance in demanding

workstation environments. And, to assure access to the latest productivity enhancing technology solutions, Dell invests in the workstation ISV community by providing the hardware platforms needed to further multithreaded and 64-bit application development. By maintaining strong relationships with ISV application developers, Dell engineers can provide ongoing optimization and support, should you need it.

Advanced remote access to the performance of the Dell Precision R5400

The full performance of the Dell Precision R5400 can be accessed by using the optional Dell FX100 Remote Access Device. Part of Dell's Flexible Computing initiative, this solution (host card and remote user portal) benefits from having dedicated hardware running Teradici® PC-over-IP® (PCoIP) technology that leaves the workstation's CPU and network resources available to run the chosen applications. A more flexible and low-cost alternative to traditional wired KVM remote solutions, the Dell FX100 can deliver an outstanding remote user experience (network infrastructure dependent). For virtual remote desktop environments (no host card needed) the Dell FX100² is a certified PCoIP Hardware Zero Client with VMware View™ 4 enabling simple plug-and-play access to VMware View 4 Virtual Desktops. Please refer to the Dell FX100 Remote Access Device product brochure for more information on this world-class solution.

A new solution for some old challenges

The Dell Precision R5400, with the optional remote access solution, offers advanced relevant technologies designed to overcome some tough traditional challenges and succeed where other solutions have struggled to deliver:

- Centralizing critical data and applications in a secure location
- Eliminating the need for workstation users to be in inhospitable areas
- Enabling high-performance clustering using GPGPUs (General Purpose GPUs)
- Enabling flexible resource allocation (24-hour usage models)³
- Enabling faster moves and changes as project teams are reassigned — retaining benefits of a standards-based workstation
- Addressing the distance limitations of traditional wired KVM solutions with optional Dell FX100 remote access device

Dell Precision R5400 Rack Workstation Technical Specifications																	
Processors	Dual-Core (6MB L2 cache) & Quad-Core (2X 6MB L2 cache) Intel® Xeon® Processors																
Operating System	<ul style="list-style-type: none"> Genuine Windows® 7 Ultimate 32-Bit; Genuine Windows 7 Ultimate 64-Bit Genuine Windows® 7 Professional 32-Bit; Genuine Windows 7 Professional 64-Bit Genuine Windows Vista® Business 32-bit; Genuine Windows Vista® Business 64-bit Red Hat® Enterprise Linux WS v.5.3 (Also certified to run Red Hat Enterprise Linux Version 4 64-bit) 																
Chipset	Intel 5400																
Memory	Up to 32GB ⁴ quad-channel architecture fully buffered DIMM 667MHz ECC memory; in 4 DIMM slots																
Flash BIOS	BIOS 8MB flash memory for system BIOS; SMBIOS 2.5 support																
Graphics ⁵	Support for 2 PCI Express x16 graphics cards up to 150 watts (in 2 x16 Gen1 PCI-e slots). All graphics cards support dual monitors configurations <table border="0"> <tr> <td>High End 3D</td> <td>Mid-range 3D</td> <td>Entry 3D</td> <td>Professional 2D (not certified)</td> </tr> <tr> <td>NVIDIA® Quadro® 6000</td> <td>ATI FirePro V7800</td> <td>ATI FirePro V4800</td> <td>ATI FireMV™ V2260</td> </tr> <tr> <td>NVIDIA Quadro 5000</td> <td>ATI FirePro V5800</td> <td>NVIDIA Quadro 600</td> <td>NVIDIA Quadro NVS 420</td> </tr> <tr> <td>NVIDIA Quadro 4000</td> <td>NVIDIA Quadro 2000</td> <td></td> <td>NVIDIA Quadro NVS 295</td> </tr> </table>	High End 3D	Mid-range 3D	Entry 3D	Professional 2D (not certified)	NVIDIA® Quadro® 6000	ATI FirePro V7800	ATI FirePro V4800	ATI FireMV™ V2260	NVIDIA Quadro 5000	ATI FirePro V5800	NVIDIA Quadro 600	NVIDIA Quadro NVS 420	NVIDIA Quadro 4000	NVIDIA Quadro 2000		NVIDIA Quadro NVS 295
High End 3D	Mid-range 3D	Entry 3D	Professional 2D (not certified)														
NVIDIA® Quadro® 6000	ATI FirePro V7800	ATI FirePro V4800	ATI FireMV™ V2260														
NVIDIA Quadro 5000	ATI FirePro V5800	NVIDIA Quadro 600	NVIDIA Quadro NVS 420														
NVIDIA Quadro 4000	NVIDIA Quadro 2000		NVIDIA Quadro NVS 295														
GPU	NVIDIA Tesla C1060 GPU; NVIDIA Tesla S1070 1U GPU (Graphics Processing Unit for High-Performance Computing, no graphics output)																
Hard Drives ⁶	Up to 2 SATA hard drives with optional RAID 0 or 1. <ul style="list-style-type: none"> Up to 2.0TB; SATA 3.0GB/s 7200 RPM with 16MB DataBurst Cache™ Up to 250GB; SATA 3.0GB/s 7200 RPM with 8MB DataBurst Cache Up to 300GB; SATA 3.0GB/s 10K RPM with 8MB DataBurst Cache 																
Hard Drive Controller	Integrated SATA 3.0GB/s controller that supports host-based (software) RAID 0, 1																
Communications	Integrated: Dual Broadcom® NetXtreme 10/100/1000 Gigabit Ethernet controllers Optional: IEEE 1394a card; Broadcom® NetXtreme 10/100/1000 Gigabit Ethernet controller PCI Express® card																
Audio	Integrated high-definition audio (Rev 1.0 Specification) with Sigmatel STAC9200 High-Definition Audio CODEC and Intel ESB2's integrated AC97/ high-definition digital controller.																
Standard I/O	Six USB 2.0: two on front panel, three on back panel, and one internal; two serial; two PS/2; two RJ-45; stereo line-in and line-out on back panel																
Bays	Two internal 3.5" hard disk drive bays; one external 5.25" slim-line optical bay																
Slots	All full height and full length slots accommodated in two risers: <ul style="list-style-type: none"> Riser 1: two standard PCIe x16 Gen 1 full length graphics slots each with 150W (300W total) Riser 2: either: (1) PCIX 64-bit @ 100MHz; (1) PCIe x16, wired as x8 (default) Or (1) PCIX 64-bit @ 100MHz; (1) PCI 32-bit; 5V 																
Chassis (2U Rack)																	
Dimensions	27" (68.5cm) D x 17.5" (44.4cm) W x 3.4" (8.6cm) H without bezel attached																
Peripherals																	
Monitors	Performance flat-panel displays, Dell UltraSharp™ widescreen and standard flat-panel displays from 17" viewable to 30" viewable																
Keyboard	Dell Enhanced Quietkey™ USB; Enhanced Multimedia USB; Smart Card keyboard USB																
Mouse	Dell USB two-button mouse and Dell USB optical two-button scroll mouse																
Optional Speakers	Internal chassis speaker; Dell two- and three-piece stereo system; Dell sound bar for all flat-panel displays																
Storage Devices																	
Optional Removable Storage	CD-RW/DVD Combo; DVD-ROM; DVD+/-RW; USB external floppy drive																
Security																	
Software	Trusted Platform Module 1.2 (TPM 1.2); chassis intrusion switch; Setup/BIOS password; I/O interface security																
Hardware	Front bezel key lock, top chassis cover lock																
Environmental & Regulatory																	
	You can find additional safety best practices information on the Regulatory Compliance homepage on www.dell.com/regulatory_compliance																
Service & Support																	
Base	3-Year Limited Warranty ⁷ with 3-year standard Next-Business-Day (NBD) on-site ⁸ parts replacement and 3-year NBD on-site service ⁸																
Recommended	Dell ProSupport is designed to rapidly respond to your business' needs, protect your investment and sensitive data, and provide enhanced proactive support services to help reduce risk and complexity within your IT environment																

Learn more at dell.com/Precision

¹ ISV certification applies to select configurations

² VMware View™ 4 PCoIP® Hardware zero client support on the Dell FX100 requires PCoIP firmware release 3.X.

³ Microsoft may require a Remote Desktop license for the Dell FX100 under certain serial usage models. Please consult with Microsoft for details.

⁴ Up to 1GB may not be available with 32-bit operating systems due to system resource requirements.

⁵ Significant system memory may be used to support graphics, depending on system memory size and other factors.

⁶ GB means 1 billion bytes and TB equals 1 trillion bytes; actual capacity varies with preloaded material and operating environment and will be less.

⁷ For a complete copy of our guarantees and limited warranties, please write Dell U.S.A. L.P., Attention: Warranties, One Dell Way, Round Rock, TX 78682. For more information visit www.dell.com/warranty

⁸ May be provided by third-party. Technician dispatched, if necessary, following phone-based troubleshooting. Availability varies. See dell.com/service contracts for details.

Teradici® and PC-over-IP® are registered trademarks or trademarks of Teradici Corporation in the United States and/or other countries. Microsoft, Windows and Windows Vista are trademarks or registered trademarks of Microsoft Corporation in the U.S. and other countries. Dell's Terms and Conditions of Sales and Service apply and are available upon request. Dell cannot be held responsible for errors in typography or photography. Dell PCs use genuine Microsoft® Windows. Dell is a trademark of Dell Inc. ©2010 Dell Inc. All rights reserved.

